

UNCLASSIFIED

AD 280 135

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

2828

(10)

280135

AD No. _____
ASTIA FILE COPY

Released to ASTIA
by the Research and
Development Dept., U.S.
Naval Propellant Plant

TMR 191

EFFECT OF GAMMA IRRADIATION FROM
A COBALT-60 SOURCE UPON THE SENSITIVITY OF
ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6

Title Unclassified

6 November 1961

280 135



U. S. NAVAL PROPELLANT PLANT,

INDIAN HEAD, MARYLAN

RESEARCH AND DEVELOPMENT DEPARTMENT

Joe L. Browning, Director

Technical Memorandum Report 191

6 November 1961

**EFFECT OF GAMMA IRRADIATION FROM
A COBALT-60 SOURCE UPON THE SENSITIVITY OF
ELECTRIC IGNITION ELEMENTS MK 2, MK 4, and MK 6**

By

Title Unclassified

**Y. K. Roots
T. D. Phillips**

U. S. NAVAL PROPELLANT PLANT

Indian Head, Maryland

**O. A. WESCHE
Captain, USNavy
Commanding Officer**

**J. E. DODGEN
Commander, USNR
Technical Director**

FOREWORD

The work described in this report was done under Task Assignment 506-925/56035/0204. The original data is reported on laboratory notebook pages 20476 through 20549. Data are as of 18 September 1959.

A. J. Matuszko
Head, Fundamental
Process Division

Approved by:

Bodo Bartocha
Associate Director
for Research

Released by:

O. A. WESCHE
Captain, USNavy
Commanding Officer

CONTENTS

<u>Heading:</u>	<u>Page no.</u>
Foreword _____	iii
Abstract _____	vi
Experimental _____	1
Results and Conclusions _____	5
References _____	9

FIGURES

1. Squib Sample Firing Record _____	3
2. Squib Test Firing Apparatus _____	4
3. Sensitivity of Mk 2 Squibs Subjected to Gamma Irradiation _____	6
4. Sensitivity of Mk 4 Ignition Elements as Affected by Gamma Irradiation _____	7
5. Sensitivity of Mk 6 Ignition Elements as Affected by Gamma Irradiation _____	8

Abstract Unclassified

ABSTRACT

Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a cobalt-60 source. Dosages ranged from 1.75×10^5 to 78.23×10^5 roentgens. The effect of this irradiation on the sensitivity of the elements in terms of time-to-ignition was variable. The Mk 6 elements showed a general tendency toward decreased sensitivity; the Mk 2 elements showed less tendency toward decreased sensitivity; and the Mk 4 elements showed an increase in sensitivity.

**EFFECT OF GAMMA IRRADIATION FROM
A COBALT-60 SOURCE UPON THE SENSITIVITY OF
ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6**

A testing program has been conducted to determine the effect of gamma irradiation on electric explosive devices (EED). This report covers the results of testing irradiated Mk 2, Mk 4, and Mk 6 electric ignition elements. The Mk 2 and Mk 6 elements contain 90 mg of FFFG black powder and an ignition charge of lead styphnate and cellulose nitrate in a 50:1 ratio. The Mk 4 element contains 200 ± 25 mg ignition charge of lead styphnate and graphite in a 96:4 ratio. The balance of this 325-mg element is black powder. The sensitivity of EED's after they had been given dosages of from 1.75×10^5 roentgens to 78.23×10^5 roentgens was compared to that of similar EED's that had received no irradiation. The cobalt-60 source used in this work was obtained from the Brookhaven National Laboratories, Upton, New York, (see Reference 1 for description) and was calibrated April 15, 1957, as 1330 curies, with an intensity of radiation along the central axis of the source of 568,000 roentgens per hour. Assuming the half life of cobalt-60 to be 5.2 years, the dosage rate for the exposure of these EED's was computed from the Radiological Health Handbook.⁽²⁾ The dosage was then calculated by multiplying the dosage rates so obtained by the time of irradiation.

EXPERIMENTAL

When an explosive is placed in a radiation source, the hazard cannot be predicted in advance. Possibilities exist that the substance might ignite and explode within the source or may become sensitive to handling during subsequent tests. For this reason, preliminary tests were carried out by placing an EED in an iron capsule and giving it an exposure in excess of any contemplated during the series of tests. Such a test having given reasonable assurance of safety, the EED's were packed in cylindrical aluminum canisters in groups of 10 to 30 and in such a way that all would receive equal irradiation when the canisters were lowered by chain hoist into the source. Exposures ranged from a few hours to a few days.

Both the irradiated and the nonirradiated EED's were fired in the ramp-firing equipment devised by Phillips and Klein.⁽³⁾ The effect of irradiation on the sensitivity of the EED was determined by the increase or decrease of the firing time (t_f) for the various irradiation doses. The firing time (t_f) (see Figure 1) is the time from the moment the current is initiated in the bridge wire (A) until the instant when the blast from the squib takes place (B). The former is determined by the recording galvanometer in the firing circuit and the latter by the time when the photoelectric cell detects the flash from the squib. Time until the squib blast might also be determined by measuring to the instant at which a break (C) is found in the firing line curve, except that the bridge wire of the EED does not always break or fuse at the instant of the explosion of the EED.

Figure 2 shows the arrangement of the essential items of apparatus used in obtaining the firing data. On the table top at left is a C.E.C. Recorder (A) with its attached camera (B) while in the center is the fire control box (C) and at the right, fabricated partly of plexiglass, is the safety firing chamber (S), its door (R), and firing circuit interlock (P,Q). Within the firing chamber is a massive steel and lead firing block (I) with holes drilled to hold the various squibs and other EED's. The white dot (J) is an EED positioned for firing. The EED lead wires are attached to the alligator clips (O), and when the door (R) is closed these are connected by interlocks (P,Q) to the firing line which is energized by the switch (E). In front of the table, supported on a small shelf is a photoelectric cell (L) and its accompanying voltage supply (M). Wires (N) lead from the photoelectric cell to the galvanometer (A). The window of the photoelectric cell (L) faces the EED (J) from outside the transparent front wall of the safety firing chamber (S).

The EED (J) is mounted securely in the vertical member of the massive steel and lead firing block (I). A smaller central hole behind (T) permits the insulated lead wires to be drawn through to make connections with firing-line alligator clips at (O). A safety feature of this firing arrangement is the safety chamber where the firing circuit from (C) terminates at (G); two lines from this point, one leading to the voltmeter (H) and the other to the interlock (P,Q) on the door (R) give indication of the presence of voltage in the door (R) at the interlock (P,Q) which would cause the squib to fire if the door was closed.




FIGURE 1. SQUIB SAMPLE FIRING RECORD




FIGURE 2. SQUIB TEST FIRING APPARATUS

Pressing on the button (D) and pushing switch (E) forward sets the camera into operation and after a millisecond delay applies voltage to the firing line to explode the EED.

On a shelf below the table are storage batteries (T) which supply the following approximate d-c voltages: the recorder, 24 volts; the firing-box relay, 48 volts; the firing line, 68 or more volts. Batteries are kept charged by a selenium recharger (U).

RESULTS AND CONCLUSIONS

From the graphs and the tabulated data given in Figures 3, 4, and 5, it will be observed that the roentgen dosages range from 1.75×10^5 to 78.23×10^5 roentgens and that the effect of these dosages on the firing time of the squibs is extremely variable. The Mk 6 ignition elements show a general tendency toward decreased sensitivity, as shown by the increased time to ignition; the Mk 2 elements show less tendency toward decreased sensitivity. In the case of the Mk 4 ignition elements, however, the sensitivity increases and no explanation for the difference is available. It should be noted that the range over which these elements were exposed exceeds that which they would probably experience in combat conditions save near ground zero in an atomic blast.⁽⁴⁾ The data here presented indicate that in so far as hazard due to irradiation of gamma rays from nuclear installations is concerned, any such installation which is sufficiently shielded for safety of personnel would be adequately safe for electric explosive devices such as those here considered. Hence, we can say that there appears to be no hazard in the transport of EED's in atomic-powered craft from the standpoint of gamma irradiation.




FIGURE 3. SENSITIVITY OF MK 2 SQUIBS SUBJECTED TO GAMMA IRRADIATION




FIGURE 4. SENSITIVITY OF MK 4 IGNITION ELEMENTS AS AFFECTED BY GAMMA IRRADIATION




FIGURE 5. SENSITIVITY OF MK 6 IGNITION ELEMENTS
AS AFFECTED BY GAMMA IRRADIATION

REFERENCES

- (1) Bernard Manowitz. "Facilities for Gamma Irradiation." Nucleonics. 11:18-20 (1953).
- (2) U. S. Department of Health, Education, and Welfare. RADIO-LOGICAL HEALTH HANDBOOK. Compiled and edited by Simon Kinsman. January 1957. p. 104.
- (3) U. S. Naval Propellant Plant. A RAMP-TYPE TESTING CIR-CUIT FOR ELECTRIC EXPLOSIVES DEVICES. By A. H. Klein and T. D. Phillips. Memorandum Report No. 155. 3 November 1958. UNCLASSIFIED
- (4) U. S. Atomic Energy Commission. THE EFFECTS OF NUCLEAR WEAPONS. Washington, D. C.: U. S. Government Printing Office. June 1957.

2

DISTRIBUTION LIST

<u>Addressee</u>	<u>Copy no.</u>
Naval Propellant Plant (Archives copy)	1
U. S. Department of the Interior Bureau of Mines 4800 Forbes Street Pittsburgh 13, Pennsylvania Attn: Marjorie P. Benoy, Repts. Librarian Explosives Research Laboratory	2
National Aeronautics & Space Administration 1520 H Street, N. W. Washington 25, D. C. Attn: Chief, Division of Research Information	3-9
Commander Air Force Flight Test Center Edwards Air Force Base, California Attn: FTRS	10
Commander Wright Air Development Division Wright-Patterson Air Force Base Ohio Attn: WCLJC	11
Commander Air Proving Ground Center Eglin Air Force Base Florida Attn: Technical Library	12
Commander Air Force Ballistic Missile Division Hq. Air Res. and Dev. Command P. O. Box 262 Inglewood, California Attn: WDSOT	13

Commander
Armed Services Tech. Information
Agency
Arlington Hall Station
Arlington 12, Virginia
Attn: TIPCR 14-23

Commander
Air Force Flight Test Center
Edwards Air Force Base, California
Attn: FTRP 24

Commander
Air Force Missile Development Center
Holloman Air Force Base
New Mexico
Attn: MDGRTL, Technical Library 25

Commanding General
Aberdeen Proving Ground
Maryland
Attn: Ballistic Research Laboratories
ORDBG-BLI 26-27

Commanding General
USA Ordnance Arsenal, Frankford
Philadelphia 37, Pennsylvania
Attn: Propellant and Explosives
Section, 1331 28-29

Commanding Officer
Ordnance Office
Duke Station
Durham, North Carolina 30

Commanding Officer
Picatinny Arsenal
Dover, New Jersey
Attn: Library 31-32

Commander
Army Rocket and Guided Missile Agency
Redstone Arsenal
Alabama
Attn: Technical Library
ORDXR-OTL 33-36

Commanding General
White Sands Missile Range
New Mexico
Attn: ORDBS-OM-TL 37-39

Commanding Officer
Radford Arsenal
Radford, Virginia 40

Commanding General
Ordnance Ammunition Command
Joliet, Illinois
Attn: ORDLY-AREL, Engr. Library 41

Commanding Officer
Diamond Ordnance Fuze Laboratories
Washington 25, D. C.
Attn: ORDTL (012) 42

Commander
Army Ballistic Missile Agency
Redstone Arsenal, Alabama
Attn: ORDAB-HSI 43

Bureau of Naval Weapons
Department of the Navy
Washington 25, D. C.
Attn: DLI-3 44-45

Bureau of Naval Weapons
Department of the Navy
Washington 25, D. C.
Attn: RMMP-2 46

Bureau of Naval Weapons
Department of the Navy
Washington 25, D. C.
Attn: RMMP-331 47

Commander
U. S. Naval Weapons Laboratory
Dahlgren, Virginia
Attn: Technical Library 48

Commander
U. S. Naval Ordnance Laboratory
White Oak
Silver Spring, Maryland
Attn: Library 49-50

Commander
U. S. Naval Ordnance Test Station
China Lake, California
Attn: Technical Library Branch 51-53

Director
U. S. Naval Research Laboratory
Washington 20, D. C.
Attn: Chemistry Division, Code 6130
R. R. Miller 54

Bureau of Naval Weapons
Department of the Navy
Washington 25, D. C.
Attn: CS 55

Department of the Navy
Office of Naval Research
Washington 25, D. C.
Attn: Code 426 56

Bureau of Naval Weapons
Department of the Navy
Washington 25, D. C.
Attn: SP-27 57

Radiation Effects Information Center Battelle Memorial Institute 505 King Avenue Columbus 1, Ohio Attn: Richard E. Bowman		58-60
Atomic Energy Commission Washington, D. C.		61-63
Thiokol Chemical Corporation Redstone Division Huntsville, Alabama Attn: Technical Director		64-65
Reaction Motors Division Thiokol Chemical Corporation Denville, New Jersey Attn: Librarian		66
Aerojet General Corporation P. O. Box 296 Azusa, California Attn: Librarian		67
British Joint Services Mission The BNS/MOSS Scientific and Technical Information Section P. O. Box 680 Benjamin Franklin Station Washington, D. C. Attn: Technical Information Officer	Via: Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: DSC	68-71
Defence Research Member Canadian Joint Staff (W) 2450 Massachusetts Ave., N. W. Washington 8, D. C.	Via: Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: DSC	72-75
Dr. Charles S. Waring Asst. Technical Director of Research U. S. Naval Ordnance Test Station China Lake, California		76

Monsanto Chemical Company Special Projects Department Everett, Massachusetts Attn: Dr. Lucius Gilman	77
Commander Wright Air Development Division Wright-Patterson Air Force Base Ohio Attn: WCLTRP	78
Commanding Officer Office of Naval Research 1030 E. Green Street Pasadena 1, California	79
Atomic Energy Commission Office of Technical Information Extension P. O. Box 62 Oakridge, Tennessee	80
U. S. Naval Ordnance Laboratory Corona, California Attn: Code 44	81
Polaris Project Management Office, NPP	82
Quality Assurance Department, NPP	83
Production Department, NPP	84
Research and Development Department, NPP	85-101
Naval Propellant Plant Files	102-106

<p>Naval Propellant Plant, Indian Head, Maryland (TMR 191)</p> <p>EFFECT OF GAMMA IRRADIATION FROM A COBALT-60 SOURCE UPON THE SENSITIVITY OF ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6. By Y. K. Roots and T. D. Phillips. 6 Nov. 1961. 9 p.</p> <p>UNCLASSIFIED</p> <p>Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a (over)</p>	<p>1. Igniters - Effects of radiation</p> <p>2. EED's - Effects of radiation</p> <p>I. Roots, Y. K.</p> <p>II. Phillips, T. D.</p>	<p>Naval Propellant Plant, Indian Head, Maryland (TMR 191)</p> <p>EFFECT OF GAMMA IRRADIATION FROM A COBALT-60 SOURCE UPON THE SENSITIVITY OF ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6. By Y. K. Roots and T. D. Phillips. 6 Nov. 1961. 9 p.</p> <p>UNCLASSIFIED</p> <p>Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a (over)</p>	<p>1. Igniters - Effects of radiation</p> <p>2. EED's - Effects of radiation</p> <p>I. Roots, Y. K.</p> <p>II. Phillips, T. D.</p>	<p>Naval Propellant Plant, Indian Head, Maryland (TMR 191)</p> <p>EFFECT OF GAMMA IRRADIATION FROM A COBALT-60 SOURCE UPON THE SENSITIVITY OF ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6. By Y. K. Roots and T. D. Phillips. 6 Nov. 1961. 9 p.</p> <p>UNCLASSIFIED</p> <p>Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a (over)</p>	<p>1. Igniters - Effects of radiation</p> <p>2. EED's - Effects of radiation</p> <p>I. Roots, Y. K.</p> <p>II. Phillips, T. D.</p>
<p>Naval Propellant Plant, Indian Head, Maryland (TMR 191)</p> <p>EFFECT OF GAMMA IRRADIATION FROM A COBALT-60 SOURCE UPON THE SENSITIVITY OF ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6. By Y. K. Roots and T. D. Phillips. 6 Nov. 1961. 9 p.</p> <p>UNCLASSIFIED</p> <p>Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a (over)</p>	<p>1. Igniters - Effects of radiation</p> <p>2. EED's - Effects of radiation</p> <p>I. Roots, Y. K.</p> <p>II. Phillips, T. D.</p>	<p>Naval Propellant Plant, Indian Head, Maryland (TMR 191)</p> <p>EFFECT OF GAMMA IRRADIATION FROM A COBALT-60 SOURCE UPON THE SENSITIVITY OF ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6. By Y. K. Roots and T. D. Phillips. 6 Nov. 1961. 9 p.</p> <p>UNCLASSIFIED</p> <p>Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a (over)</p>	<p>1. Igniters - Effects of radiation</p> <p>2. EED's - Effects of radiation</p> <p>I. Roots, Y. K.</p> <p>II. Phillips, T. D.</p>	<p>Naval Propellant Plant, Indian Head, Maryland (TMR 191)</p> <p>EFFECT OF GAMMA IRRADIATION FROM A COBALT-60 SOURCE UPON THE SENSITIVITY OF ELECTRIC IGNITION ELEMENTS MK 2, MK 4, AND MK 6. By Y. K. Roots and T. D. Phillips. 6 Nov. 1961. 9 p.</p> <p>UNCLASSIFIED</p> <p>Electric ignition elements Mk 2, Mk 4, and Mk 6 have been exposed to gamma radiation from a (over)</p>	<p>1. Igniters - Effects of radiation</p> <p>2. EED's - Effects of radiation</p> <p>I. Roots, Y. K.</p> <p>II. Phillips, T. D.</p>

<p>Cobalt-60 source. Dosages ran from 1.75×10^5 to 78.23×10^5 roentgens. The effect of this irradiation on the sensitivity of the elements in terms of time-to-ignition was variable. The Mk 6 elements showed a general tendency toward decreased sensitivity; the Mk 2 elements showed less tendency toward decreased sensitivity; and the Mk 4 elements showed an increase in sensitivity.</p>		<p>Cobalt-60 source. Dosages ran from 1.75×10^5 to 78.23×10^5 roentgens. The effect of this irradiation on the sensitivity of the elements in terms of time-to-ignition was variable. The Mk 6 elements showed a general tendency toward decreased sensitivity; the Mk 2 elements showed less tendency toward decreased sensitivity; and the Mk 4 elements showed an increase in sensitivity.</p>	
<p>Cobalt-60 source. Dosages ran from 1.75×10^5 to 78.23×10^5 roentgens. The effect of this irradiation on the sensitivity of the elements in terms of time-to-ignition was variable. The Mk 6 elements showed a general tendency toward decreased sensitivity; the Mk 2 elements showed less tendency toward decreased sensitivity; and the Mk 4 elements showed an increase in sensitivity.</p>		<p>Cobalt-60 source. Dosages ran from 1.75×10^5 to 78.23×10^5 roentgens. The effect of this irradiation on the sensitivity of the elements in terms of time-to-ignition was variable. The Mk 6 elements showed a general tendency toward decreased sensitivity; the Mk 2 elements showed less tendency toward decreased sensitivity; and the Mk 4 elements showed an increase in sensitivity.</p>	